

SECTION C-C





"Access 455" Electrically Operated Aluminium Roller Shutter Door.

Specification: -

Shutter curtain constructed from 55mm extruded mill finish aluminium hollow laths running in aluminium side guides with brush seals. The shutter curtain is suspended from a suitable steel tube, mounted between aluminium endplates at high level. The door is provided as standard with a two part aluminium coil casing.

Operation: -

Electrical operation is by means of high quality single-phase tubular motor and gearbox fitted within the barrel assembly.
An emergency manual hand crank over-ride is provided as standard to allow operation of the door in case of power failure (provided on door side of opening only).

Electrical Operation (240v c/w Wiring)

Electrical operation by means of 240 volt, single phase 'tubular motor operator, mounted within barrel assembly. All electrical wiring is by means of S-Y & Y-Y cabling. If conduit or alternative is required this is available at extra cost.
Please note that a power supply MUST be available at time of installation. Clients to provide mains supply terminated at a fused spur positioned within 1 metre of final motor position

Notes:
" Unless stated otherwise fused spur to be on same side of opening as door.
" Unless otherwise stated, all activating and/or control equipment (e.g. push buttons) will be located within 1000mm of structural opening.

INCLUSIONS:-

REV	BY	DATE	DESCRIPTION

CLIENT:-

SITE:-

SCALE AT A3:- 1:5
DATE:-
DRAWN:-
CHECKED:-

DRAWING NUMBER | **REV**

No ."ACCESS 455" DOOR(s)

ADVANCED DOORS LTD.
Park Mill Way
Clayton West Ind. Est.
Clayton West
Huddersfield
West Yorkshire
HD8 9XJ
Tele (01484) 861112
Fax (01484) 861056
email:info@advanceddoors.co.uk
internet: www.advanceddoors.co.uk