

FLEXIBLE DOORS

PVC Strip Curtains & Crash Doors

SPECIFICATION: -

PVC Strip curtain in 2mm, 3mm and 4mm thickness dependant on application. Polar grade is also available for sub zero temperatures.

APPLICATION: -

Each curtain is purpose-made to suit site dimensions and requirements and is suitable for all types of use and compliments our Rolling Shutters and Thermalex doors. Sliding track arrangements are available so that a portion or the entire curtain can be easily moved. Red safety strips are provided at each end of the curtain as standard.



SPECIFICATION: -

Door Frame manufactured from 63mm o/d mild steel tube to British Standard, welded to a mild steel flat, and suitably strengthened by a corner box section. The frame to be complete with double acting spring mechanisms located at the top of the vertical tube section.

The frame to be complete with double acting spring mechanisms located at the top of the vertical tube section. The frame pivots on fitting plates, which, unless otherwise instructed, will be provided for securing directly to the underside of the lintel and to the floor. The main frame is generally finished in two coats of etch primer paint.

Door Panels comprising nominal 8mm thick reinforced rubber across the lower section, and nominal 10mm thick all clear high grade PVC across the upper section. The joint between the two materials being affected by means of overlapping rubber wear strips. The panels are complete with a tapered overlap.

Can be supplied fully automatic with our pneumatic drive system.

APPLICATION: -

Each door is purpose-made to suit site dimensions and requirements and is suitable for all types of use.

ADVANCED DOORS LTD
 PARK MILL WAY, CLAYTON WEST,
 HUDDERSFIELD, WEST YORKSHIRE, HD8 9XJ.

TEL: (01484) 861112 FAX: (01484) 866700
www.advanceddoors.co.uk



ADVANCED DOORS LTD
 14 BEITH DRIVE
 AIRDRIE, ML6 9XN.

TEL: (01236) 766229 FAX: (01236) 763876
www.advanceddoors.co.uk