

VIKING STAR V Roller Shutter Door

SPECIFICATION:-

The shutter curtain is constructed from suitable interlocking galvanised steel laths and galvanised "T" section bottom rail, running in galvanised steel side channels, mounted on mild steel / galvanised steel support angles which are bolted to the structure.

The curtain is supported from a suitable steel tube barrel assembly at high level, running on steel bearings. The barrel assembly is supported between mild steel endplates.

A pad lockable chain keep is fitted to the drive side of the door for safe keeping/locking of the emergency haul chain.

All mild steel components are finished in one coat of primer.

Doors for openings above 4500mm wide are fitted with our tested wind anchor guide system as standard.



APPLICATION:-

Each door is purpose-made to suit dimensions and requirements and is suitable for all types of industrial use where insulation is not

OPERATION: -

Electrical operation is by means of high quality three phase motor and gearbox, incorporating digital limits. All control panels are low voltage and have open, close and emergency stop buttons as standard along with self diagnostics and service reminder.



Emergency manual over ride is provided as standard to allow operation of the door in case of power failure. A SAFETY BRAKE is fitted to the non-drive end of the barrel assembly to prevent uncontrolled dropping of shutter curtain.

BS 13241 compliant & CE Marked

OPTIONAL EXTRAS: -

- Plastisol coated laths
- Galvanised steel coil casings
- Rubber bottom seals
- Wicket Gates
- Polyester powder coat finish
- Special electrical automation and safety devices.

ADVANCED DOORS LTD
PARK MILL WAY, CLAYTON WEST,
HUDDERSFIELD, WEST YORKSHIRE, HD8 9XJ.

TEL: (01484) 861112 FAX: (01484) 866700
www.advanceddoors.co.uk



ADVANCED DOORS LTD
14 BEITH DRIVE
AIRDRIE, ML6 9XN.

TEL: (01236) 766229 FAX: (01236) 763876
www.advanceddoors.co.uk